

MAGIC: WATER REPELLANT & PROTECTOR

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

MAGIC is a deep penetrating, siloxane water repellent which produces a transparent protective barrier across the surface of a stone. MAGIC fills the pores and capillaries of the stone, and forms an invisible, vapor permeable membrane across the surface. This coating repels moisture from the surface while allowing the stone to breathe. MAGIC has no visible film, and leaves surfaces looking natural with no change in appearance.

MAGIC inhibits mold, mildew, and efflorescence, as well as damage caused by the constant absorption and evaporation of water from the stone. MAGIC penetrates immediately, deeply, and effectively, providing a long-lasting protective barrier. Use when a **natural look** is desired. For interior or exterior use.

RECOMMENDED SURFACES

- Concrete
- Travertine
- Marble
- Unglazed Tile
- Granite
- Stone, Brick, & Clay Pavers
- Grout Joints
- Shell Stone

COVERAGE

For very porous surfaces: 1st coat: 100-200 sq. ft./gallon. **2nd coat** 250-400 sq. ft./gallon.

For average density surfaces: 1st coat: 200-300 sq. ft./gallon. **2nd coat** 400+ sq. ft./gallon

For very dense surfaces: 1.5x avg. density coverage
Generally, the sealer will go twice as far on the 2nd coat as it did on the 1st coat.
Second coat can be applied immediately after the first.



SURFACE PREPARATION

Always be sure the surface is clean, dry, and free from any dirt, grease, oil, wax, or other contaminant. Read the entire label before using. Use only as directed. Always test on a small piece of material or a small inconspicuous area to determine suitability. Ensure the area is well ventilated. Ideal surface temperature should be between 60°F and 80°F. Product works best when it is the first substance applied to the surface, insuring proper penetration.

APPLICATION

MAGIC may be applied with spray applicator, brush, roller, or lint free rag. Apply liberally with a heavy first coat. Avoid puddles by spreading or wiping up excess.

FOR SEALING GROUT JOINTS: Apply to joint with small brush or squeeze bottle. Allow to soak 10-15 mins. Wipe off excess from tile surface. Do not leave voids and puddles.

MAGIC cures completely in 24 hours. High traffic areas can easily be spot treated when required because MAGIC does not build up or alter the appearance of the surface.

TECHNICAL SUPPORT

Support is available by calling (813) 876-5914

Emergency Support: ChemTel: 1(800) 255-3924

STORAGE AND HANDLING

CAUTION: Highly flammable & combustible liquid and vapor. Do not handle until all safety precautions have been read and understood. **Handling:** Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mists. Keep container closed and tightly sealed when not in use. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. **Conditions for safe storage:** Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

Materials to avoid: Do not store with the following product types: Strong oxidizing agents, Explosives, Gases.

FIRST AID MEASURES

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists. **Skin Contact:** Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists. **Inhalation:** If inhaled, remove to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. In case of unconsciousness, place patient stably on side position for transportation. **Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

VOC: 0.509 lb./gallon, 61.06 g/L

PACKAGING

1 qt: 12 units per case (28lbs)

1 gallon, 6 units per case (47lbs)

5 gallon, (39lbs)

55 gallon, (450lbs)

TRANSPORTATION

UN number: UN1139

UN proper shipping name: Coating Solution

Transport hazard class: 3

Packing group: 3

MANUFACTURER

Catalina Chemical Co.

4709 N. Lois Ave. Tampa, FL 33614