

PLUS IMPREGNATOR: WATER & OIL REPELLENT

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

PLUS is a heavy-duty impregnating sealer that produces a transparent barrier, repelling water and oils. It chemically reacts with the stone, forming a durable, long lasting, protective membrane throughout the stone and across its surface. PLUS internally seals the substrate, allowing water vapor to breathe out of the stone while preventing moisture from penetrating the surface.

PLUS penetrates immediately, deeply, and effectively, providing a long-lasting protective barrier. Surfaces treated with PLUS will retain a natural appearance with no shine or gloss. PLUS is extremely effective in areas frequently exposed to water and oils, such as kitchens, bathrooms, driveways, pools, and outdoor grill areas. PLUS also inhibits staining from food, drinks, wine, coffee, and other common spills, making maintenance easier. For interior or exterior use.

RECOMMENDED SURFACES

- Concrete
- Travertine
- Granite
- Unglazed Tile
- Marble
- Stone, Brick, & Clay Pavers
- Grout Joints

COVERAGE

For very porous surfaces: 1st coat: 100-200 sq. ft./gallon. **2nd coat** 250-400 sq. ft./gallon.

For average density surfaces: 1st coat: 200-300 sq. ft./gallon. **2nd coat** 400+ sq. ft./gallon

For very dense surfaces: 1.5x avg. density coverage
Generally, the sealer will go twice as far on the 2nd coat as it did on the 1st coat.

Second coat can be applied immediately after the first.



SURFACE PREPARATION

Always be sure surface is clean, dry, and free from any dirt, grease, oil, wax, or other contaminant. Read the entire label before using. Use only as directed. Always test on a small piece of material or a small inconspicuous area to determine suitability. Ensure the area is well ventilated. Ideal surface temperature should be between 60°F and 80°F. Product works best when it is the first substance applied to the surface, insuring proper penetration.

APPLICATION

PLUS may be applied with spray applicator, brush, roller, or lint free rag. Avoid puddles by wiping up excess.

FOR SEALING GROUT JOINTS: Apply to joint with small brush or squeeze bottle. Allow to soak 10-15 mins. Wipe off excess from tile surface. Do not leave voids and puddles. PLUS cures completely in 2-7 days. High traffic areas can easily be spot treated when required because PLUS does not build up or alter the appearance of the surface.

TECHNICAL SUPPORT

Support is available by calling (813) 876-5914
Emergency Support: ChemTel: 1(800) 255-3924

STORAGE AND HANDLING

CAUTION: Highly flammable & combustible liquid and vapor. Do not handle until all safety precautions have been read and understood. **Handling:** Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mists. Keep container closed and tightly sealed when not in use. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. **Conditions for safe storage:** Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

Materials to avoid: Do not store with the following product types: Strong oxidizing agents, Explosives, Gases.

FIRST AID MEASURES

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists. **Inhalation:** If inhaled, remove to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. In case of unconsciousness place patient stably in side position for transportation. **Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

VOC: 0.581 lb./gallon, 69.58 g/L

PACKAGING

1 qt: 12 units per case (28lbs)
1 gallon, 6 units per case (47lbs)
5 gallon, (39lbs)
55 gallon, (450lbs)

TRANSPORTATION

UN number: UN1139
UN proper shipping name: Coating Solution
Transport hazard class: 3
Packing group: 3

MANUFACTURER

Catalina Chemical Co.
4709 N. Lois Ave. Tampa, FL 33614