



SEALER 329: Natural Finish Penetrating Sealer

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

Sealer 329 is a heavy-duty, water-based impregnating sealer which protects stone, tile, and grout from stains, water damage, and corrosion. Sealer 329 penetrates deeply and effectively, chemically reacting with the stone to form a durable, transparent barrier. Sealer 329 will block water and oil molecules from penetrating the surface but will allow water vapor to breathe out of the stone. Sealer 329 can be used before grouting to serve as a grout release. Sealer 329 is a water based, environmentally friendly formulation with a low VOC composition. Surfaces treated with Sealer 329 retain their natural appearance with no visible film. For interior or exterior use.

RECOMMENDED SURFACES

- Travertine
- Shell Stone
- Limestone
- Marble
- Granite
- Unglazed Tile
- Stone, Brick, & Clay Pavers
- Grout Joints

COVERAGE

Most surfaces: 250-300 square feet per gallon

For very porous surfaces: 1st coat: 100-200 sq. ft./gallon. **2nd coat** 250-300 sq. ft./gallon.

For very dense surfaces: 500+ square feet per gallon
Second coat can be applied 30 minutes after the first.



SURFACE PREPARATION

Always be sure surface is clean, dry, and free from any dirt, grease, oil, wax, or other contaminant. Read the entire label before using. Use only as directed. Always test on a small piece of material or a small inconspicuous area to determine suitability. Ensure the area is well ventilated. Ideal surface temperature should be between 60°F and 80°F. Product works best when it is the first substance applied to the surface, insuring proper penetration.

APPLICATION

Sealer 329 may be applied by roller, brush, sprayer, or another suitable applicator. Be sure surface is clean, dry, and free from any dirt, grease, oil, or wax. Apply sealer liberally, thoroughly wetting the entire surface area. Allow 30 minutes to dry and apply a second coat. Any sealer not absorbed completely in about 10 minutes should be wiped off with a clean rag and allowed to dry. Product begins to cure within 4 hours, and completely cures in 24-48 hours. High traffic areas can easily be spot treated when required because SEALER 329 does not build up or alter the appearance of the surface.

TECHNICAL SUPPORT

Support is available by calling (813) 876-5914

STORAGE AND HANDLING

Handling: Do not get in eyes. Keep container closed and tightly sealed when not in use.

Conditions for safe storage: Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

FIRST AID MEASURES

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists.

Skin Contact: Wash with soap and water. Seek medical attention if irritation persists.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Immediately seek medical professional. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.

Emergency Support: ChemTel: 1(800) 255-3924

VOC: 0.02 lb./gallon, 2.88 g/L

PACKAGING

1 qt: 12 units per case (28lbs)

1 gallon, 4 units (37lbs) or 6 units per case (56lbs)

5 gallon, (49lbs)

55 gallon, (520lbs)

TRANSPORTATION

Proper shipping name:

Class 55 Floor Product

Non-Hazardous

Non-Flammable

MANUFACTURER

Catalina Chemical Co.

4709 N. Lois Ave. Tampa, FL 33614