

IMPREGNATING SEALER COMPARISON



Name	MAGIC	PLUS IMPREGNATOR	SEALER 329
Description	MAGIC is a deep penetrating, siloxane water repellent which produces a transparent protective barrier across the surface of a stone. MAGIC fills the pores and capillaries of the stone, and forms an invisible, vapor permeable membrane across the surface. This coating repels moisture from the surface while allowing the stone to breathe. MAGIC has no visible film, and leaves surfaces looking natural with no change in appearance. MAGIC inhibits mold, mildew, and efflorescence, as well as damage caused by the constant absorption and evaporation of water from the stone. MAGIC penetrates immediately, deeply, and effectively, providing a long-lasting protective barrier.	PLUS is a heavy-duty impregnating sealer which produces a transparent, water and oil repellent barrier. PLUS chemically reacts with the stone's surface, forming a durable, long lasting, protective membrane throughout the stone and across its surface. PLUS is extremely effective in areas frequently exposed to water and oils, like kitchens, bathrooms, driveways, pools, and outdoor grill areas. PLUS will inhibit staining from food, drinks, wine, coffee, and other common spills, and make maintenance easier. PLUS is non film forming, and leaves surfaces with a natural appearance.	Sealer 329 is a heavy-duty, water-based, impregnating sealer. It produces a transparent, durable barrier which protects from water, oils, and stains. Sealer 329 works by chemically reacting with the stone. It forms a protective membrane across the surface and blocks the pores and capillaries of the stone. Sealer 329 will block water and oil molecules from penetrating the surface but will allow water vapor to breathe out of the stone. Sealer 329 is a water based, environmentally friendly formulation with a low VOC composition. Surfaces treated with Sealer 329 retain their natural appearance with no visible film. For interior or exterior use.
Finished Look	Natural Finish No Film or Gloss	Natural Finish No Film or Gloss	Natural Finish No Film or Gloss
Excels on	Brick, Brick Pavers, Travertine, Marble, Granite, Unglazed Ceramic Tile, Clay Tiles, European Clay Pavers, Concrete, Grout Joints, Saltillo Tiles	Travertine, Marble, Terrazzo, Concrete, Brick, Stone, Unglazed Tile, Exposed Aggregate, Deep Cut Brick Pavers, Slate, Quarry Tile	Travertine, Marble, Terrazzo, Concrete, Brick, Stone, Unglazed Tile, Exposed Aggregate, Deep Cut Brick Pavers, Slate, Quarry Tile
Coating Time	Subsequent coats can be applied 15-30 minutes after the first coat. Product completely cures in 24-48 hours.	Subsequent coats can be applied 15-30 minutes after the first coat. Product completely cures in 48 hours.	Subsequent coats can be applied 15-30 minutes after the first coat. Product completely cures in 24-48 hours.
Coverage	For most surfaces: 1st coat: 200-300 sq.ft./gallon. 2nd coat 400+ sq.ft./gallon. For very porous surfaces: 1st coat: 100-200 sq.ft./gallon. 2nd coat 250-400 sq.ft./gallon. For very dense surfaces: 400+ sq.ft./gallon. Generally, the sealer will go further on a 2nd coat than it did on the 1st coat.		
Application	Sealer may be applied with spray applicator, brush, or short nap roller, or lint free rag. Apply the first coat liberally to ensure proper penetration, bonding, and to provide a good base. Avoid puddles by spreading excess.		



Visit CatalinaChemical.com for complete product information

Technical Support: (813) 876-5914