



RE-MUV-IT: Heavy Duty Sealer Remover

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

RE-MUV-IT is a heavy-duty stripper designed to remove the buildup of acrylic sealers from stone, tile, or other hardscape surfaces. RE-MUV-IT will break down most acrylic coatings to liquid form and allow the sealer to be removed from the surface.

RECOMMENDED SURFACES

- Mexican Saltillo
- Concrete
- Brick
- Stone
- Unglazed Tile
- Exposed Aggregate
- Deep Cut Brick Pavers
- Travertine
- Shell Stone

COVERAGE

Coverage of 250-400 square feet per gallon.

INSTRUCTIONS

Apply liberally with a natural fiber bristle paint brush, paint roller, or other suitable applicator, working in small areas at a time (approximately 10 sq. ft.). Let stripper stand for 5-10 minutes or until sealer begins to soften. Scrub with stiff bristle brush, pressure washer, or with other suitable tools to remove dissolved sealer. Wipe up material with a mop or rag and dispose of properly. Repeat this process, if necessary, to remove any remaining deposits. BE SURE TO REMOVE ALL RESIDUE BEFORE RE-SEALING FLOOR. USE WITH ADEQUATE VENTILATION

NOTE: Always test product on material before applying on a commercial scale to determine suitability.

STORAGE AND HANDLING

CAUTION: Highly flammable & combustible liquid and vapor. Do not handle until all safety precautions have been read and understood.

Handling: Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mists. Keep container closed and tightly sealed when not in use. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Conditions for safe storage: Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

Materials to avoid: Do not store with the following product types: Strong oxidizing agents, Explosives, Gases.



PACKAGING

1 gallon, 6 units per case (54lbs)
5 gallon, (42lbs)
55 gallon, (540lbs)

TRANSPORTATION

UN number: UN1139
UN proper shipping name: Coating Solution
Transport hazard class: 3
Packing group: 3

MANUFACTURER

Catalina Chemical Co.
4709 N. Lois Ave. Tampa, FL 33614

TECHNICAL SUPPORT

Support is available by calling (813) 876-5914
Emergency Support: ChemTel: 1(800) 255-3924

FIRST AID MEASURES

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.

Inhalation: If inhaled, remove to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. In case of unconsciousness place patient stably on side position for transportation.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.