



# SEALER 444

## PRODUCT DATA SHEET

### PRODUCT DESCRIPTION

SEALER 444 is a milky white, light viscosity, high solids content, non-toxic, water-based sealer, that dries to a very tough, slip resistant, and clear glossy finish. Formulated to efficiently seal rough or porous surfaces preventing moisture and dirt from penetrating the surface. Designed to resist fading or discoloring and maintain a gloss/wet look for long periods of time. Releases no toxic fumes, safe and easy to use when being applied in enclosed areas without the dangers of fumes or fire hazards. Use when a **high gloss or wet look** is desired. For interior or exterior use.



### RECOMMENDED SURFACES

- Mexican Saltillo
- Travertine
- Unglazed Tile
- Terrazzo
- Stone, Brick, & Clay Pavers
- Any surface where gloss is desired

### COVERAGE

**For very porous surfaces: 1st coat:** 75-150 sq. ft./gallon. **2nd coat** 150-300 sq. ft./gallon.

**For average density surfaces: 1st coat:** 200-300 sq. ft./gallon. **2nd coat** 400+ sq. ft./gallon

*Generally, the sealer will go twice as far on the 2nd coat as it did on the 1st coat.*

*Wait 6-12 hours between coats to ensure the previous one is completely dry*

### SURFACE PREPARATION

Always be sure surface is clean, dry, and free from any dirt, grease, oil, wax, or other contaminant. Read the entire label before using. Use only as directed. Always test on a small piece of material or a small inconspicuous area to determine suitability. Ensure the area is well ventilated. Ideal surface temperature should be between 60°F and 80°F. Product works best when it is the first substance applied to the surface, insuring proper penetration.

### APPLICATION

SEALER 444 may be applied with spray applicator, brush, roller, or lint free rag. Apply the first coat liberally to ensure proper penetration, bonding, and to provide a good base. Avoid puddles by wiping up excess.

**FOR SEALING GROUT JOINTS:** Apply to joint with small brush or squeeze bottle. Allow to soak 10-15 mins. Wipe off excess from tile surface. Do not leave voids and puddles.

**SMOOTH SURFACES:** apply 444 with a lint free cloth, spray applicator or short nap roller.

**ROUGH SURFACES:** apply with a ½ to ¾ inch nap paint roller or paint brush.

**VOC:** 0.068 lb./gallon, 8.17 g/L

### STORAGE AND HANDLING

**Handling:** Do not get in eyes. Keep container closed and tightly sealed when not in use.

**Conditions for safe storage:** Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

### TECHNICAL SUPPORT

Support is available by calling (813) 876-5914

### PACKAGING

1 qt: 12 units per case (28lbs)

1 gallon, 6 units per case (56lbs)

5 gallon, (49lbs)

55 gallon, (560lbs)

### TRANSPORTATION

Proper shipping name:

Class 55 Floor Product

Non-Hazardous

Non-Flammable

### MANUFACTURER

Catalina Chemical Co.

4709 N. Lois Ave. Tampa, FL 33614

### FIRST AID MEASURES

**Eye Contact:** Flush eyes with water. Seek medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. Seek medical attention if irritation persists.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Immediately seek medical professional. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.