



TERATONE 467: COLOR ENHANCING SEALER

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

TERATONE 467 is a color enhancing, slow drying, deep penetrating, solvent based acrylic sealer for interior or exterior use. TERATONE 467's slow drying nature allows it to penetrate deep before setting. Will **enhance** the natural colors of most surfaces. Very effective at sealing and protecting dense and smooth surfaces such as quarry tile, ceramic tile, slate, unfinished marble, terrazzo, travertine, smooth cement, and all other cementitious materials. Recommended for use on surfaces when **NO gloss** or a **SATIN** finish is desired.

RECOMMENDED SURFACES

- Travertine
- Brazilian & Spanish Tile
- Unglazed Tile
- Marble
- Stone, Brick, & Clay Pavers
- Exposed Aggregates
- Quarry Tile

COVERAGE

For very porous surfaces: 1st coat: 150-200 sq. ft./gallon. **2nd coat** 300-400 sq. ft./gallon.

For average density surfaces: 1st coat: 250-300+ sq. ft./gallon. **2nd coat** 400+ sq. ft./gallon.

For very dense surfaces: 1.5x avg. density coverage
Generally, the sealer will go twice as far on the 2nd coat as it did on the 1st coat.

Allow 24 hours between coats.



SURFACE PREPARATION

Always be sure surface is clean, dry, and free from any dirt, grease, oil, wax, or other contaminant. Read the entire label before using. Use only as directed. Always test on a small piece of material or a small inconspicuous area to determine suitability. Ensure the area is well ventilated. Ideal surface temperature should be between 60°F and 80°F. Product works best when it is the first substance applied to the surface, insuring proper penetration.

APPLICATION

TERATONE 467 may be applied with spray applicator, brush, roller, or lint free rag. Spread evenly and uniformly- cover entire area, leaving no puddles. Avoid puddles by wiping up excess. Allow 24 hours between coats to ensure it has dried completely. No buffing required.

SMOOTH SURFACES: apply TERATONE with a lint free cloth or short nap roller.

ROUGH SURFACES: apply with a ½ to ¾ inch nap paint roller or paint brush.

TECHNICAL SUPPORT

Support is available by calling (813) 876-5914

Emergency Support: ChemTel: 1(800) 255-3924

STORAGE AND HANDLING

CAUTION: Highly flammable & combustible liquid and vapor.

Do not handle until all safety precautions have been read and understood.

Handling: Do not get in eyes, on skin, or on clothing. Do not breathe vapors or mists. Keep container closed and tightly sealed when not in use. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

Conditions for safe storage: Keep in tightly closed, properly labeled containers. Keep in a cool, well-ventilated place.

Materials to avoid: Do not store with the following product types: Strong oxidizing agents, Explosives, Gases.

VOC: 1.09 lb./gallon, 130.66 g/L

PACKAGING

1 qt: 12 units per case (28lbs)

1 gallon, 6 units per case (45lbs)

5 gallon, (40lbs)

55 gallon, (445lbs)

TRANSPORTATION

UN number: UN1139

UN proper shipping name: Coating Solution

Transport hazard class: 3

Packing group: 3

MANUFACTURER

Catalina Chemical Co.

4709 N. Lois Ave. Tampa, FL 33614

FIRST AID MEASURES

Eye Contact: Flush eyes with water. Seek medical attention if irritation persists.

Skin Contact: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.

Inhalation: If inhaled, remove to fresh air. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. In case of unconsciousness place patient stably in side position for transportation.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Rinse mouth with water. Seek medical attention if symptoms appear.